

Key Technology and Features: See pages 32-35 for details.









PN: 1140560













AT PRO™ INTERNATIONAL KEY FEATURES

- ★ Pro Mode Audio: Proportional Audio and Tone Roll Audio features allow user to hear subtle changes in target's response to better judge its conductivity, size, shape, depth.
- ★ High-Res Iron Discrimination™: Allows user to set iron discrimination to one of 40 levels for precise ability to separate good targets from trash.
- ★ Digital Target ID: 0 to 99 Target ID scale offers increased ability to distinguish one target's conductivity from another.
- ★ Iron Audio™: Allows the user to hear discriminated iron and to alter the detector's mid-tone signal's range.
- ★ Fast Recovery Speed: Allows greater ability to pick out good targets amongst trash.
- ★ All Terrain Versatility: Weatherproof housing designed for dusty, humid or wet environments; unit can be submerged to a maximum 10-foot depth.
- 15 kHz frequency: Improved detection of small targets, gold nuggets,
- Ground Balance: Automatic and manually adjustable for improved performance.
- Graphic Target Analyzer™ (GTA): Identifies target's conductivity.
- Continuous Coin Depth Indicator: to determine target depth.
- Battery Condition Indicator: shows battery life continually.

Search Modes (Discrimination Patterns): 6 plus electronic pinpointing

• Select from Custom, Zero or Coins in Standard Mode or in Pro Mode

• Pinpoint

Land headphones included PN: 2202400





ADVANCED IRON ID

SELECT FROM STANDARD OR PRO AUDIO MODES.

Target ID Cursor Segments	20
Iron Discrimination Segments	40
Notch Discrimination	Adjustable
Search Modes	6 (3 Standard, 3 Pro modes)
Sensitivity/Depth Adjustments	8
Electronic Pinpointing	YES
Frequency	15 kHz, user adjustable
Audio Tone ID Levels	3
Standard Searchcoil	8.5" x 11" DD PRO formance™
Length (Adjustable)	43" to 56" (1.09m - 1.4m)
Total Weight	3.03 lbs. (1.4 kgs.)
Batteries	4 AA (included)
Battery Condition Indicator	YES
Warranty	2 Year, Limited Parts/Labor
AT PRO searchcoils and accessories, see page 28-30.	



